



Cold Stop® Insulated Curtains

"Energy Savings 33% +"

Cold Stop® curtains, originated and designed by Seymour Manufacturing International (SMI), provide a revolutionary alternative to plastic strip curtains used in many Coldrooms. The curtains are a cost efficient thermal barrier based on Temprowhich gives the curtains unique insulation properties far greater than standard types, and resultant energy reductions. Floor ice and its associated hazards are reduced.

Cold Stop® curtains are available in standard widths of 300mm and bespoke heights with deep, clear windows. They are quickly and easily installed.

Cold Stop® curtains are energy efficient and provide reduced wear on evaporator equipment allowing optimum settings to quickly achieve an internal working temperature.

Although proved with sensitive thermal imaging equipment it is hard to believe the outside temperature of Cold Stop® curtains in a freezer can register at 10°C and the inside surface recorded at -21°C. A 31°C difference.

- **Temprow Cold-Stop® Insulated curtains provides minimum energy savings of 25% in chillers to 33% plus in freezers.**
- **Maximum return on investment in a minimum time period.**
- **Soft and user friendly and cannot be removed easily by staff.**
- **Low maintenance; easily cleaned, hygienic and easy to repair or replace should damage occur.**
- **Curtains are light, flexible, fit well and do not split thus avoiding the expense of frequent costly replacement.**



- **Field trials indicate the life of the curtain is 5 to 6 times longer than PVC strip types, providing substantial capital savings.**
- **Unique 'cold lock' system ensures that curtains fit neatly and effectively to the floor and ceiling, saving costly energy.**
- **Unique patented header arrangement is a design and efficiency breakthrough.**

Thermal Information

Below is a table showing the results attained by Campden BRI during testing:

Product	Thermal Resistance			Thermal
	Tog	Clo	K Value m ² K/W	U Value W/(m ² K)
TF25 Temprow 25mm Standard	6.6	4.26	0.66	1.52
TF12 Temprow 12mm Light Duty	5.4	3.48	0.54	1.85

Figures may be improved when Temprow is matched with different face or lining materials or if a heavier Temprow core specification is demanded. Temprow is Fire Retardant to BS 5867: Pt 2 1980.

Temprow Technical information and trial results available.

Temprow has been shown to save up to 33% on energy bills and significantly reduce your carbon footprint. Below are typical figures gathered showing savings we would expect from these standard door sizes (These were taken with an ambient of 15°C and an internal temperature of -17°C).

Door Size	ROI (in months)
Cold Stop Curtains to fit 900mm by 2300mm high	5.7
Cold Stop Curtains to fit 1000mm by 2300mm high	5.2
Cold Stop Curtains to fit 1400mm by 2300mm high	5.2
Cold Stop Curtains to fit 1600mm by 2300mm high	4.7
Cold Stop Curtains to fit 1800mm by 2300mm high	4.7



Typical Users of Temprow

Supermarkets

Wholesalers

Catering Companies

Transport Companies

Pharmaceutical

Chemicals

Warehouses

Bakeries

Dairies

Laboratories

Food Processors

Hotels

Medical

Liquor Merchants

Delicatessen

Available from:



BigBear Refrigeration & Air Conditioning

Call 1300 244 232 or email info@bigbearsw.com.au

www.bigbearsw.com.au